

The logo for AR PANEL, featuring the brand name in a bold, white, sans-serif font. The text is centered between two horizontal white lines that have a slight break in the middle, giving it a modern, architectural feel.


AR PANEL

PRODUCT DATA SHEET


Wall sandwich panel

AR PANEL S MiWo MXL

- standard fastening system



CROSS SECTION





PARAMETERS

Core thickness	100	120	150	160	180	200
External facing thickness [mm]	0,5 -0,7					
Internal facing thickness [mm]	0,5 -0,7					
Core density	113 ± 10% kg/m³					
Weight [kg/ m²]	20,3	22,6	26,1	27,2	29,5	31,8
Proper acoustic insulation [Rw(C,Ctr) dB]	31 (-1,-3)	31 (-2,-3)				
Sound absorption [αw]	0,15					
Heat transfer coefficient Ud,S = W/(m2 x K)	0,4	0,33	0,27	0,25	0,22	0,2
Reaction to fire	A2-s1,d0					
Fire spread according to PN-B-02867	NRO					





Installation details are available in the fire classifications of ARPANEL sandwich panels.



PARAMETERS

Core thickness	100	120	150	160	180	200
INTERNAL WALL						
Fire resistance according to EN 13501-2 vertical	E 120/ EI 60 ≤ 4 m E 90/ EI 60 ≤ 7,5 m	E 120/ EI 120/ EW 120 ≤ 4 m E 90/ EI 90/ EW 90 ≤ 7,5 m	E 240 / EI 240 ≤ 4 m E 180 / EI 180 ≤ 7,5 m			
Fire resistance according to EN 13501-2 horizontal	E 60/ EI 60/ EW 60 ≤ 6 m E 45/ EI 45/ EW 45 ≤ 7,5 m	E 180/ EI 120/ EW 180 ≤ 4m E 120/ EI 120/ EW 120 ≤ 7,5m	EI 180/ EW 180 ≤ 6 m EI 120/ EW 180 ≤ 7,5 m	E 240/ EI 240/ EW 240 ≤ 4 m E 180/ EI 180/ EW 180 ≤ 7,5 m E 120/ EI 120 ≤ 8 m E 90/ EI 90 ≤ 10m		
EXTERNAL WALL						
Fire resistance according to EN 13501-2 vertical	E 120 (o↔i)/ EI 60 (o↔i) ≤ 4 m E 90 (o↔i)/ EI 60 (o↔i) ≤ 7,5 m	E 120 (o↔i)/ EI 120 (o↔i)/ EW 120 (o↔i) ≤ 4 m E 90 (o↔i)/ EI 90 (o↔i)/ EW 90 (o↔i) ≤ 7,5 m	E 240/ EI 240 (o↔i) ≤ 4 m E 180/ EI 180 (o↔i) ≤ 7,5 m			
Fire resistance according to EN 13501-2 horizontal	E 60 (o↔i)/ EI 60 (o↔i)/ EW 60 (o↔i) ≤ 6 m E 45 (i↔o)/ EI 45 (i↔o)/ EW 45 (i↔o) ≤ 7,5 m	E 180 (o↔i) / EI 120 (o↔i)/ EW 180 (o↔i) ≤ 4 m E 120 (o↔i)/ EI 120 (o↔i)/ EW 120 (o↔i) ≤ 7,5 m	EI 180 (o↔i)/ EW 180 (o↔i) ≤ 6 m EI 120 (o↔i)/ EW 180 (o↔i) ≤ 7,5 m	E 240 (o↔i)/ EI 120 (o↔i)/ EW 240 (o↔i) ≤ 4 m E 180 (o↔i)/ EI 120 (o↔i)/ EW 180 (o↔i) ≤ 7,5 m E 120 (i→ o)/ EI 120 (i→ o) ≤ 8 m E 90 (i→ o)/ EI 90 (i→ o) ≤ 10 m		

PROFILES

Name	external	internal	cross-section
Micro 8	✓	✗	
Micro 14	✓	✗	
Linear	✓	✓	
Smooth	✓	✓	
Micro 20	✗	✓	
Micro 30	✓	✗	

TYPES OF STANDARD COATINGS

Polyester – PE


*Other types of coatings, e.g. PVDF, PUR PA, HDX, PRISMA, FOODSAFE, HPS, INOX, SDP, are available upon request.

ENVIRONMENT IN CASE OF A STANDARD COATING, POLYESTER – PE

A possibility to apply inside, in environments A1, A2, A3 and outside buildings C1, C2, C3.

*For environments characterized by higher aggressiveness, a coating that meets the requirements of a given corrosivity category should be selected.

STANDARD COLORS



Ask our representative about the availability of other standard colors of ARPANEL sandwich panels.

AVAILABLE LENGTHS OF PANELS

Standard lengths of panels are from 2,0 m to 14,5 m.

PERMISSIBLE DEVIATIONS FROM DIMENSIONS

According to EN 14509:

Panels with length of ≤ 3 m ± 5 mm

Panels with length of > 3 m ± 10 mm

For the covering width of the sandwich panel, ± 2 mm

At the panel thickness:

For $D \leq 100$ mm ± 2 mm

For $D > 100$ mm ± 2 %

Rectangularity of cut at the length $\leq 0,6$ % of the panel width

Panel:

2 mm per each meter of length, but not more than 20 mm

8,5 mm per each meter of width, but not more than 10 mm

The presented contents and drawings are demonstrative material only. Adamietz Sp z o.o, the producer of sandwich panels ARPANEL, is not responsible for any differences between the content of the product card and the real products parameters. The producer reserves the right to implement changes and modifications to the content without prior notice. Pursuant to the Civil Code, the content of the product card does not constitute a commercial offer.

Adamietz Sp z o.o., the producer of sandwich panels ARPANEL, is the copyright holder of the materials included in this product card. The content of the materials is protected by the copyright. The sale, publication, licensing or any distribution of the part or the whole of these works is prohibited without the written consent of Adamietz Sp. z o.o.

The design of these materials and the information concerning the offered products are the property of the Adamietz company. Copying and the reproduction of the materials by third parties in conducting business activity without information on their origin will constitute an act of unfair competition.